

DECODALLE

CORK WALL TILES TECHNICAL SPECIFICATION

	Veneered agglomerated cork tiles, to be used as interior
	wallcovering, in accordance with EN 12781.
Description	Tiles have a decorative cork veneer adhered on a core of
	agglomerated cork (painted in selected articles). Tiles are
	cut in the dimensions of 600x300 mm and have a thickness
	of 3 mm. The surface is fine sanded, painted (in selected
	articles) and finished with a wax-based product.
Dimensions	600 x 300 x 3 mm
	PARAWAX
Finish	Wax based product developed specially for cork, with good
	flexibility, abrasion, and moisture/water repellence.
Product structure	
Product structure	Finish layer: PARAWAX
Product structure	Finish layer: PARAWAX Veneer: Natural and agglomerated cork veneer
Product structure	,
Product structure	Veneer: Natural and agglomerated cork veneer



TECHNICAL DATA		
Length and width	EN ISO 24342	600 x300 mm ± 0.5 %
Overall thickness	ISO 7322	3 mm ± 0.2 mm
Squareness Straightness	EN ISO 24342	< 0.4 mm < 0.3 mm
Apparent density	ISO 7322	290 Kg/m3
Mass per unit area	EN ISO 23997	870 g/m2 ± 10 %
Tensile strength	ISO 7322	> 700 kPa



Produit à base de cire développé spécialement pour le liège, offrant une bonne flexibilité, une bonne abrasion et une bonne résistance à l'humidité et à l'eau.



Technologie d'agglomération de liège sans formaldéhyde, sans PVC et sans phtalates.













