

GROOVY

CORK WALL TILES TECHNICAL SPECIFICATION

GENERAL DEFINITION AND PRODUCT COMPOSITION			
	Solid agglomerated cork tiles, to be used as interior		
	wallcovering, in accordance with EN 12781.		
Description	Tiles are shaped by CNC machining, cut in the dimensions		
·	of 600x300 mm and have a thickness of 6 mm.		
	The grooves are coloured by digital printing and the surface is finished with a waterbased protector for increased water and stain resistance.		
Dimensions	600 x 300 x 6 mm		
	CORKGUARD®		
	Aqueous dispersion based on SCOTCHGARD™ and a		
Finish	combination of resins, designed to provide excellent		
	water, oil and stain repellent properties on natural cork.		
	With CleanSurface powered by Microban® antimicrobial		
	technology.		



Product structure

Finish: CORKGUARD®. Colour: Digital print.

Core: CNC machined agglomerated cork.

Installation Glued, according to installation instructions.



TECHNICAL DATA			
Length and width	EN ISO 24342	600 x 300 mm ± 0.5 %	
Overall thickness	ISO 7322	6 mm ± 0.2 mm	
Squareness Straightness	EN ISO 24342	< 0.4 mm < 0.3 mm	
Apparent density	ISO 7322	290 Kg/m3	
Mass per unit area	EN ISO 23997	1740 g/m2 ± 10 %	
Tensile strength	ISO 7322	> 1000 kPa	



Dispersion aqueuse basée sur SCOTCHGARD™ et une combinaison de résines, conçue pour conférer au liège naturel d'excellentes propriétés hydrofuges et anti taches.



Technologie d'agglomération de liège sans formaldéhyde, sans PVC et sans phtalates.



Protection antibactérienne intégrée dans la finition de surface, grâce à la technologie exclusive Microban®.













