

## **RUSTIC**

## **CORK WALL TILES TECHNICAL SPECIFICATION**

	Patchwork cork tiles or panels produced by gluing and pressing several pieces of natural raw cork to be used as wallcoverings within buildings.  Standard dimensions are 900 x 600 and 600 x 300 mm and				
Description					
				the thickness can vary from 20 to 35 mm depending on the	
				type of texture. The surface can be natural or coloured.	
	Dimensions	900 x 600 mm 600 x 300 mm			
		Bark Sandstone Slate			
Product structure					

Installation

Surface: Rough cork bark or natural cork. Backing: Agglomerated cork (Bark and Sandstone)

Glued, according to installation instructions.



## LANDSCHRECK UNIVERSE

TECHNICAL DATA		
Length and width	EN ISO 24341	900 x 600 mm ± 1 % 600 x 300 mm ± 1 %
Overall thickness		20 to 35 mm
Squareness Straightness	EN ISO 24342	< 1 mm
Mass per unit area	EN ISO 23997	Bark: 7.5 Kg/m2 ± 10 % Sandstone: 6.5 Kg/m2 ± 10 % Slate: 4.9 Kg/m2 ± 10 %
Dimensional variation	EN ISO 23999	< 1 %
Moisture content	EN 12105	< 10 %
Reaction to fire	EN ISO 11925- 2 EN 13501-1	Extent of flame < 150 mm. No flaming droplets. Fire class E



Technologie d'agglomération de liège sans formaldéhyde, sans PVC et sans phtalates.













